



SK Series

Compression Splicing Kit Features:

- Molded from high impact resistant polycarbonate.
- No water absorption characteristics.
- Excellent dielectric properties.
- Available in two, three and four wire kits.
- Supplied with EC1410 wire connectors for #14-#10 gauge wire.
- **Third party certified to NSF/ANSI 372.**



LA302R

LA300 Series Lightning Arrestor Features:

- LA302 Rated 125-250V, single phase, 3 wire Light Duty service.
- Maximum Current: 60,000 amps on LA302.
- Maximum Energy per pole: 2000 joules on LA302.
- Unlimited number of surges.
- N-4 Weatherproof enclosure.
- Use with 1/2" or 3/4" locknut for knock-out installation.
- ETL Listed



HPL

Pump Light Features:

- Can be used with two or three wire motors in either 115 volt or 230 volt applications.
- It is easy to install at the pressure switch, where it is used to indicate that the pump is running or at the control box, where it is used to indicate that current is available to the submersible pump.

Part Number	Description	# Tubes	# Connectors	Ctn Qty	List Price
Compression Splice Kits					
SK2	#14, #12, #10	2	2	50	\$ 10.12
SK3	#14, #12, #10	3	3	50	13.67
SK4	#14, #12, #10	4	4	50	16.75
Lightning Arrestors					
LA302R	125/250 V, Single phase, 3 wire, 2 1/4" x 2 1/4"			18	115.19
Pump Light					
HPL75	Pump Light			12	22.99