



WTC6 ABS PLASTIC WATERTIGHT WELL CAP

Features:

- Fits 6" ID, 6 1/4" OD well casing
- 1 1/4" NPT conduit tap for easier large wire installations.
- Hi-impact blue ABS plastic with UV inhibitors for strength and resistance to heat, cold and corrosion.
- Oversize, flexible well casing gasket seal to provide vermin-proof and tamper resistant installation.
- Heavy duty stainless steel nuts, bolts and washers for corrosion resistance and dependable gasket sealing.
- Sturdy vent system uses two downward facing 9/16" diameter, corrosion resistance, NO LEAD brass mesh screen vents to meet state codes and PAS97 certification.
- Well log inside cap records GPM, casing feet, date installed, well depth, water depth, pump HP and pump setting.
- ANSI/NSF372 Low Lead certified and listed.
- Water Systems Council/PAS97 (2019)/ASSE Standard #1093-2019 certified and listed.
- WTC6L locking feature with stainless steel ring set screw with padlock locking pads. (Padlock NOT included).
- Individually cartoned with hardware and installation instructions.



Part Number	Nominal Well Casing	Maximum Casing OD	Conduit Tap	Master Ctn Qty	List Price
WTC6	6" and 6 1/4"	6 5/8"	1 1/4"	10	\$77.61
WTC6L	6" and 6 1/4"	6 5/8"	1 1/4"	10	77.93

Custom personalization of the caps above is available. Add "P" suffix to part number. Self adhering, engraved brushed aluminum tag. Minimum of 24 of one size.

Do NOT overtighten screws, nuts or set screw. Overtightening will cause well cap to crack and will void warranty.