

## Well Caps - Cast Aluminum







AWTC--T Series





**Nominal Well** 

SC Series C Series

## **AWTC-Series Watertight Vermin- Proof Cap Features:**

- · Cast aluminim for strength and weather resistance.
- · All stainless bolts and ground screws.
- · Molded 3/16" gasket.

## **SC-Series Watertight Cap Features:**

- · For use on plastic casing only.
- Injection molded ABS & grade 319 aluminum, can be solvent welded directly to PVC well casing.
- · Stainless steel nuts, bolts & screened vents.
- All SC Series well caps are certified and approved water tight to ASSE Standard #1093-2019 and WSC PAS-97 (2019) standards.

## C-Series Standard Conduit Cap Features:

· For use on steel or plastic casing.

Conduit

· Stainless steel set screws.

Casing

Custom personalization of the caps above is available. Add "P" suffix to part number. Self adhering, engraved brushed aluminum tag. Minimum of 25 of one size.

Vent

Ctn

List



Part Number	Casing Size	0.D.	Conn.	Size	Weight	Qty	Price
A I	Landinka Manada - Da	( ) W . II ( ) .					
	tertight Vermin-Pr			a !!		0.5	<u> </u>
AWTC4	4"	4 1/2"	1"	1"	2.2	25	\$ 146.28
AWTC45 ☺	4 1/2"	5"	1"	1"	2.7	20	198.74
AWTC5	5"	5 9/16"	1"	1"	2.4	20	176.56
AWTC55 ☺	5 1/2"	6"	1"	1"	3.1	15	218.45
AWTC6	6"	6 5/8"	1 1/4"	1"	2.8	15	185.22
AWTC7 ☺	6 1/2"	7"	1 1/4"	1"	3.1	13	257.51
AWTC8	8"	8 5/8"	1 1/4"	1"	4.3	1	384.48
AWTC10	10"	10 3/4"	2"	1" (2)	9.0	1	981.97
AWTC12	12"	12 3/4"	2"	1" (2)	11.0	1	2029.35
© Fits Whitewa	ater pitless units						
	tertight Vermin-Pr	oof Well Ca	p w/ 1-1/4	Top Ta	for use w/	pellet cl	hlorinators
AWTC45T ☺	4 1/2"	5"	1"	1"	2.7	20	234.18
AWTC55T ☺	5 1/2"	6"	1"	1"	3.1	15	253.35
AWTC6T	6"	6 5/8"	1 1/4"	1"	2.8	15	185.22
© Fits Whitewa	ater pitless units						
Aluminum/AB	S Combination Wa	tertight Wel	l Cap				
SC4	4"	4 1/2"	1 "		1.5	12	93.78
SC45	4 1/2"	4.95"	1 "		1.7	15	97.01
SC5	5"	5 9/16"	1 "		2.3	10	107.02
SC6	6"	6 5/8"	1"		2.5	8	112.07
SC614	6 1/4"(SDR27.6)	6.9"	1"		2.5	12	129.54
Standard Vent	ilated Cap with Cor	nduit Openi	ng				
C4	4"	4 1/2"	3/4"		1.6	25	77.25
C5	5"	5 9/16"	3/4"		2.0	15	108.79
C6	6"	6 5/8"	3/4"		2.3	15	117.67
C7	7"	7 5/8"	1"		2.9	15	182.80
C8	8"	8 5/8"	1"		3.4	1	197.82

