

# Tapes - PTFE Thread Seal



HTT Series



## Made in USA PTFE Thread Seal Tape Features:

- UL Listed.
- 100% virgin PTFE.

### HTT260/HTT520 Medium Density PTFE Tape

- White general purpose
- Medium density.

### HTT260-1/2SS Gray Stainless Steel PTFE Tape

- Nickel pigment added for use on all stainless steel threads.
- Prevents galling, seizing and corrosion.
- High density for coarse SS threads.

### HTT260-1/2PP Pink Plumbers PTFE Tape

- For plumbers and pipe fitters.
- Pink to signify heavier than standard or medium density.

### HTT260-1/2GAS Yellow Gas Service PTFE Tape

- For gas lines of all types- Natural gas, butane, propane.

### HTT260-1/2OXY Green Oxygen PTFE Tape

- Green for oxygen applications. Grease free.
- For all oxygen lines. Will not support combustion.

### HTT260-1/2XHD White Extra High Density PTFE Tape

- For all industrial applications.
- Can be used for water, oil, chemical, medical or food processing.

Part Number	Color	Usage	Thickness	Density	Temp Range	Specs
HTT260	White	General	3.5 mil	.90	-450°F to +550°F	Mil T-27730A
HTT520	White	General	3.5 mil	.90	-450°F to +550°F	Mil T-27730A
HTT260-1/2OXY	Green	Oxygen lines	3.5 mil	1.55	-450°F to +550°F	Mil T-27730A/AA58092
HTT260-1/2PP	Pink	Plumbing	3.5 mil	1.55	-450°F to +550°F	Mil T-27730A/AA
HTT260-1/2XHD	White	Industrial	3.5 mil	1.20	-450°F to +550°F	Mil T-27730A
HTT260-1/2SS	Light Gray	Stainless Steel	3.5 mil	1.55	-450°F to +550°F	Mil T-27730A/AA58092
HTT260-1/2GAS	Yellow	Gas lines	3.5 mil	1.20	-450°F to +550°F	Mil T-27730A

Part Number	Width	Length	Color	Case Qty	List Price
HTT260	1/2"	260 in	White	144	\$ <b>3.67</b>
HTT520	1/2"	520 in	White	144	<b>5.16</b>
HTT520-3/4	3/4"	520 in	White	144	<b>7.01</b>
HTT520-1	1"	520 in	White	144	8.25
HTT260-1/2OXY	1/2"	260 in	Green	144	<b>8.12</b>
HTT260-1/2PP	1/2"	260 in	Pink	144	<b>8.12</b>
HTT260-1/2XHD	1/2"	260 in	White	144	<b>8.12</b>
HTT260-1/2SS	1/2"	260 in	Light Gray	144	<b>8.12</b>
HTT260-1/2GAS	1/2"	260 in	Yellow	144	<b>8.12</b>